

## Superlite SL-C Specifications

Wheelbase - 105-106 inches

Front track - 75 inches measured from outside wall of tire

Rear track - 75 inches measured from outside wall of tire

Overall maximum length - 16ft

Overall maximum width - 75 inches not including mirrors or splitter endplates

Car weight without driver or fuel - 2450lbs

Front and rear wheel sizes - 11 x 18 and 11 x 13

Brake calipers - AP 5000+pro 6 pot

Brake rotor manufacturer - 380mm front, 355mm rear Wilwood/AP

Rear wing - Selig 1223-16 dual element 74inch wide w/19x22 end plate; diffuser

Front splitter - SLC/RCR race splitter (6 inch) with end plates at 76 inch total width

Engine manufacturer, type, displacement, and specifications - GM LS7 based 440cid, dart block - 4.185 bore/4 inch stroke; 12-1 comp.

Transaxle manufacturer, type, and specifications - Albins st6-m 6 speed sequential

Manufacturer's suspension components and anti-roll bars - SLC/RCR - race

Shift mechanism specifications - AIM steering wheel with electric pro shift paddles

Size and specs of radiator(s) and oil cooler - Radiator - dual pass standard Howe/Fluidyne race oil coolers and mocal trans cooler

Engine horsepower and torque peak outputs - 649rwhp @ 6700rpm; 560 torque @5700rpm

Compliance document for the car's rollover structure - car already has SCCA logbook - SPO; ICSCC logbook SPO; and NASA logbook - SU with cage cert.approval.