2024 SCCA® SOLO® SPEC COUPE OFFICIAL SPECIFICATIONS

SCCA National Solo

OBJECTIVE

To provide an affordable autocross package that combines a streetable car and a capable autocross car using specified parts.

CAR

- → 2013-16 Subaru® BRZ® (including 2015 Series.Blue and 2016 Series.HyperBlue models).
- → 2013-16 Scion® FR-S® (including 2015 Release Series 1.0 and 2016 Release Series 2.0 models).

MANDATORY PARTS

Parts specified below (tires, wheels, and suspension) must be used. All components and parts (e.g., hardware) are required to be installed. Original equipment (OE) or equivalent components are not allowed. Required bump stops are provided in the Eibach® PRO-PLUS Performance Handling Package.

Anti-roll (sway) bar end links may be substituted but may serve no other purpose. To facilitate anti-roll bar installation and adjustment through the range of operation metal spacers (e.g., washers), may be added between the anti-roll bar bracket and the subframe. The spacers must be less than 7.00 mm (0.275") thick.

TIRES

- → Falken Azenis RT660
- → Size: 225/45-17

WHEELS

- → Diameter and width (in.): 17x8 (OE 17x7 may be used only as a full set of 4 wheels.)
- → Offset, including wheel spacer (mm): +40 (40ET or ET40) or greater
- → Weight, minimum without spacer if used (lbs.): 17, including:
  - Wheel weights
  - TPMS sensor if installed
  - Tire valve stem (type unrestricted)

SUSPENSION: (EXCLUSIVELY AVAILABLE FROM TIRE RACK® - WWW.TIRERACK.COM)

- → **Eibach® PRO-PLUS Performance Handling Package, part # TR82105.880, including:**
  - 82105.001 front spring (2)
  - 82105.002 rear spring (2)
  - 1J0412303(770343) front bump stop (2), ~53mm height
  - BS770143 rear bump stop (2), ~33mm height

- 82105.320F front anti-roll bar (1)
- UB0346 front bushing (2)
- 82105.320R rear anti-roll bar (1)
- UB0347 rear bushing (1)
- 82105.310HK hardware kit (1)

→ **SPC Performance® Adjustable Alignment Kit, part # 60620T, including:**

- 81305 [(2) EZCam® XR bolts,14mm]
- 67660 [(2) rear adjustable lower control arm]
- 67655 [(2) rear adjustable toe arm]

→ **Koni® Sport (Yellow) struts/shocks with tamper proof seal**

- 8741-1560LSSC [(1) left front]
- 8741-1560RSSC [(1) right front]
- 8041-1416SSC [(2) rear]

AUTHORIZED CHANGES/MODIFICATIONS

If a change or modification is not specifically authorized, it is not allowed. All repairs must comply with factory-authorized methods and procedures, or industry standard methods, as follows: If the manufacturer does not provide an appropriate method of repair, industry standard methods and procedures may be used. Such repairs may not result in a part or combination of parts that provides a performance advantage (e.g., significant change to weight, suspension control, power, etc.) as compared to the standard part(s). Competitors are strongly cautioned to use this allowance to make common-sense repairs only.

→ Front bumpers, rear bumpers, body trim pieces and attachment points may be reinforced to prevent or repair damage from hitting cones. Reinforcements that are not visible to the exterior of the car are allowed. Such repairs and/or reinforcements may serve no other purpose.

→ Wheel spacers are allowed provided the resultant combination with the wheel complies with the offset requirements.

→ Wheel lug studs (e.g., length) and lug nuts may be changed.

→ Components which are normally expendable and considered replacement parts may be used provided they are essentially identical to the standard parts, used in the same location, and provide no performance benefit. Examples are:

- Clutch and related components (excluding flywheel).
- Hardware (nuts, bolts, clips, etc.).

→ Parts superseded by Toyota® or Subaru® may be used on either vehicle.

→ These allowances are strictly to permit components to be replaced from alternate sources other than the original manufacturer. They should not be construed as an allowance to replace components with those which could be considered a "higher performance" alternative.

→ It is not permitted to use non-compliant parts even if they have been set to the manufacturer's specifications.

BODYWORK

→ Accessories, gauges, indicators, lights and other appearance, comfort and convenience modifications which have no effect on performance and/or handling and do not materially reduce the weight of the car are permitted. This does not allow driver's seat substitutions, or the removal of "tow hooks" or "tiedown loops." Data acquisition systems (including video cameras) and the accompanying sensors are allowed but may serve no other purpose during a run than real-time display and data recording.

→ Alternate shift knobs are allowed.

→ Spare tires, tools, and jacks may be removed. Any fastening hardware and/or other pieces that can no longer be firmly secured in the absence of the spare tire may be removed if necessary to ensure compliance with Solo® Rules section 3.3.3.B.1, Safety Inspections, Inspection Requirements

→ Driver restraints as outlined in Solo® Rules section 3.3.1, Driver Restraints, are allowed. Seats may not be cut to allow for the installation of alternate seat belts or harnesses. A horizontal "harness bar" may be used as part of the installation hardware for allowed driver restraints provided it has no more than two (2) attachment points to the chassis and is bolted at those locations. A C-type harness bar may also be used; it may have four (4) bolted attachment points to the chassis (2 primary and 2 supporting connections to resist rotation). Truss-type harness bars with more than two (2) attachment points are not allowed.

→ Cars may add one (1) rear trailer hitch. Factory tie downs and cosmetic pieces (e.g., diffusers) may be modified or removed to facilitate hitch installation. Complete or partial removal of the hitch is allowed for competition, provided it does not result in a reduction in weight compared to the unmodified standard configuration.

→ Tow bar brackets may be installed and may serve no other purpose.

→ Any item not permanently in place by manufacturer-installed fasteners may be removed (i.e., emergency tool kits).

SUSPENSION

→ Alignment
- Both the front and rear suspension may be adjusted through their designed range of adjustment by use of the specified parts. No suspension part may be modified for the purpose of adjustment unless such modification is specifically authorized by the manufacturer service documentation.

→ Bushings
- Suspension bushings as supplied in the kits are mandatory.
- Those not included in the supplied kits may not be replaced with bushings of a different material or dimension.

BRAKES

→ The make and material of brake linings (pads) may be changed.

ELECTRICAL SYSTEM

→ The make of spark plugs is unrestricted.

→ No changes are permitted to electronic engine management systems or their programming.


→ Tire Pressure Monitoring Systems (TPMS) may be disabled. Altering the signal to the TPMS module is allowed.

ENGINE AND DRIVETRAIN

→ The engine air filter element may be removed or replaced provided the air flow path remains as originally designed (i.e., no additional openings). No other components of the air induction system may be removed, replaced, or modified.

→ The muffler and midpipe (as shown in the following figure) may be substituted provided the system exits the car in one or both original locations

- Weight – minimum, both muffler and midpipe (lbs.): 18



→ Oil filters are unrestricted.

→ The installation of oil catch tanks or oil separators is allowed provided the function of the PCV system remains functional.

→ An oil cooler is allowed provided no unauthorized modifications are made to perform the installation.

→ Silicone replacement hoses are allowed as alternate components provided they meet the requirements of Solo® Rules section 13, Street Category, with regard to size, shape, location, and performance equivalence. Replacement induction system air

intake hoses must also match the standard part in stiffness, contour, and internal wall texture.

→ Lubricants and fluids are unrestricted.

→ Fuel must be Federally approved for use on public highways and must not exceed an octane rating of 93 [(R+M)/2], with an allowed variance of up to +0.9. Ethanol content may not exceed 15%.

There may be clarifications issued to these SSC rules from time-to-time. Official notifications will be published in Fastrack News, posted monthly on www.scca.com.